

FR3210T











Printer Model	FR3210T	
Print Head Category	Konica1024j 6PL)	Kyocera, 4PL)
Printing Size	3200mm	
UV Lamp	UV LED light	
Rip Software	Photoprint/Onyx	Onyx/Caldera
Media Thickness	1-50mm	
Print Head NO.	4-12pcs	2-8pcs
Ink Color	CMYK/LC/LM+W	
Resolution	726*720dpi	726*900dpi
	726*1080dpi	726*1200dpi
	726*1440dpi	726*1800dpi
Ink Tank Volume	2L	
Image Format	TIFF, JPEG, POSTSCRIPT, EPS, PDF	
Printing Speed	High speed(2 Row) 68sqm/h	High speed(2 Row) 65sqm/h
	Production(2 Row) 52sqm/h	Production(2 Row) 47sqm/h
	Quality(2 Row) 35sqm/h	Quality(2 Row) 39sqm/h
Power Supply	AC 220V,50/60HZ >30A	
Enviroment	Temperature 20-28°C	
	Humidity 40-60%	
Machine Size	5890*1500*1580mm	
Machine Weight	2685kg	
Outdoor Shelf Life	2Year (use Quantum Ink)	
Warranty Time	One year	

Technical specifications, designs are subject to change without prior notice.



General info

High Precision



X Axial equipped with 1 µm metal raster, gives a high precisely ink drops control.Makes only 1 micro tolerance on Bi-direction printing.

Stable Movement



Moving belt for y axial material feeding.

User Friendly



Ink level alarm to remind operator to reload ink when ink level low.

Safety Care



Carriage installed with crash sensor, high sensitivity to ensure print head safety from accidental ly damage. Anti-static device remove static on plastic media to make sure fine quality.

S-Curve Shaft



Rear pressure shaft in S-Curve makes media feeding no wrinkle, and gives suitable pressure to rigid media.

Multi-Function



Extention table assist client to print long rigid material.

Perfect Curing



High energy LED lamp for better curing on almost all kind of material.

Fast Ajustment



According to different pritning media, table vacuum force is adjustable.

Convenient Use



Air inlfation shaft for flex media feeding and collection.

Quiet Movement



Japan THK mute guiderail makes smooth movement and low noise come true.