



Character

- High definition konica512i-30pl/720dpi printhead
- Segmented infrared heating, which can adapt to drying of different width jobs
- Carriage lift can be adjustment and can be used for printing different thickness materials
- Widened roller to prevent material from wrinkling
- Adjustable suction platform for different materials
- Spray head moisturizing ink stack, fast and safe protection printhead

Model	HDM3300 High speed heavy duty inkjet printer
Printhead	KM512i/KM1024i LNB-30PL Double Row

HDM3300 High speed heavy duty inkjet printer Configuration List

Brand Spare Part

◆ X axis Beam	Industrial Alu Beam
◆ Carriage	The lifting carriage can be manually adjusted
◆ Rip	MainTop/Ultraprit/Photoprint(option)
◆ Servo motor	Fuji/leadshine
◆ Cable	High flexibility cable
◆ Dry system	Infra-red heater&Drying system
◆ Printhead moisturizing	Industrial printhead special moisturizing device
◆ Resolution	480*360dpi 480*540dpi 360*480dpi 360*540dpi
◆ Color control	ISO ICC
◆ Environment	Temperature18°C-30°C, Humidity40%-60%
◆ VCC	One-phase AC220±20, 50-60HZ,7kw
◆ Data transfer mode	HDI
◆ Print Material	PVC flex banner/coiled material

Speed

	2pass	3pass
(4H)	140m ² /h	90m ² /h
(8H)	280m ² /h	180m ² /h

Printing size: 3200mm

Printing width: 3.2m

Machine size: (L*W*H)/Weight 4860*1000*1470mm/1000kg



Belt
Italy MEGADYNE, Mute process



Japan THK guide rail
2.0 Guide rail/Mute rail not easy to deform,high speed,long lifetime



Buffer cartridge
Continuous ink supply to prevent broken ink



Germany Igus Chain
Protect cable,modular,low noise,long lifetime