

A new generation, quality upgrading!




POWER Series

UV Roll to Roll Printer

SPARTAN RTR3200

GEN5/GEN6/KM6988H/KM1024ISHE

➔ **SPARTAN RTR3200** A masterpiece in wide-format UV printers. With outstanding performance of high precision and industrial efficiency printing, It will help to enhance your printing capability and expand your business for sure. It will be your No.1 choice for high-end printing works.




Headplate Scheme(Other Optional,MAX 12H)

Plus Your Interests



Four large diameter rubber rollers reduce the deflection and lead the material movement more smoothly and stably without deviation.



Water-cooled high-energy LED-UV curing

Convex spotlight makes stronger light to cure ink, and efficient water-recycling system ensure it works longer time.



Use Vacuum Ink supply Systems
Use Vacuum Ink supply Systems that satisfy with long time printing.



Automatic solenoid valve control of ink system

The ink valve system is opened and closed automatically by solenoid valve control.



Ink detection alarm system
When any ink barrel color ink is about to run out, this system can point out what color ink you need to add ink.



Automatic anti-static system

Anti-statics system is upgraded to eliminate statics at higher efficiency and in larger area.

Multiple printing models, Various printing applications



Rich printing solutions, Makes you RICH





With the world's top partners, to create the most outstanding quality.

TECHNICAL SPECIFICATION

Model	SPARTAN RTR3200							
Printhead	RICOH GEN5 7PL 3-12H		RICOH GEN6 5PL 3-12H		KM6988H 14PL 4-12H		KM1024iSHE 6PL 4-12H	
Resolution	600,900,1200,1800,2400 dpi					720,1080,1440 dpi		
Printing speed	60m ² /h -12H (12 Printheads CMYK x 3R)		90m ² /h -12H (12 Printheads CMYK x 3R)		105m ² /h -12H (12 Printheads CMYK x 3R)			
Color	4color/double 4 color/6 color/white or varnish Option							
Ink Curing system	LED lamp							
Air draft	4 air draft divisions adapt to the max working area dimension							
Media handling	4 rubbers Roll to Roll							
Printing size	3200mm width*MAX							
Ink	UV Curing ink							
Ink capacity	1.5L drums, automatic surveillance for shorting of ink							
Ink supply system	Auto Negative ink supply							
Media	flex banner, Car sticker, cloth,Soft film,Fiberglass Mesh,3P polyester...							
Control system	Windows7/10 64bit . RAM 8G . HDD 500G . SSD 128G . CPU Intel5							
RIP software	ONYX / Print Factory / Photoprint / Caldera Option							
Operation environment	Temperature	18℃~ 26℃ is more effectively control static and guarantee printed quality						
	Humidity	40% ~ 70%.TO effectively control static and guarantee printed quality						
Power supply	Power Maximum:5KW; AC,50HZ/60HZ; 220v(±10%) 15A							
Image format	Tiff,JPEG,EPS,PDF							
dimensions(L x W x H)	6140 x 1720 x 1925mm							
Package dimensions(L x W x H)	5860 x 1560 x 2150mm							
Net Weigh& Gross weight	2300kg & 2800kg							
Safety certification	CE Certification							

*Above specifications are subject to change without prior notice.