SPARTAN HB Series



6.6m UV Hybrid Printer SPARTAN HB6600





Comparison speed: Printing PVC

234 sqm/h 479×1080 dpi 3 pass

119 sqm/h 479×1440 dpi 6 pass



Customizable Color Combinations

Over 10 options, including C-W, W-C, C-W-C, Embossed textures

Enhanced operability and functions

New feeding up system
Special belt convey system
Four-roll printing Four times productivity



SPARTAN HB6600

^{*}speed and quality based on OMNICOLOR inks

6.6m UV Hybrid Printer

SPARTAN HB6600




Model	SPARTAN HB6600
Printhead	Konica1024a 4rows / 6rows Konica1024i 4rows / 6rows
Resolution	479,1080,1440,2160 dpi
Color	CMYK, White/Varnish, Lc, Lm (option)
Material thickness	0~25mm (0.984in)
Ink curing system	UV LED curing system
Vacuum suction	8 zones
Maximum Printing width	6600mm (259.84 in)
Ink	UV LED curable ink
Color validity	3~5 years outdoor and 7~10 years indoor without color fading (Use OMNICOLOR Inks)
Ink capacity	2.5L drums, automatic alarm for ink volum shortage
Ink supply system	Auto Negative ink supply
Media	Paper、Leather、Wallpaper、Soft film、PVC、PP、PE
PC Specification	Window7/10/11 64bit . RAM≥8G . HDD≥500G . SSD≥128G . CPU≥Inte I5
RIP software	Photoprint /Print Factory/Caldera(option)
Operation environment	Temperature / 18°C~ 26°C
	Humidity / 40% ~ 70%
Power supply	Power Maximum:14.5KW; AC,50HZ/60HZ; 380v(±10%) > 15A
Image format	Tiff,JPEG,EPS,PDF
Dimensions(LxWxH)	9500 x 2300 x 1920 mm (374.02 x 90.55 x 75.59in)
Weight	8000kg(17637lb)
Certification	CE







Printhead Soleplate



4 rows and 6 rows for KM1024a or KM1024i


Four-roll Printing Four times productivity

Taking full advantage of the 6600mm printing width, 4 media rolls (1.27m/50inch for each roll) can be mounted for simultaneous printing. Different (or same) print jobs can be printed on the 4 separate rolls. Users can select a preferred width separately for each roll. Power Pro6600 helps to shorten delivery time and reduce workload.



 st The option "4 feed-up kits" is required.

Print Speed



Dimension





^{*} Notice: above specifications are subject to change without prior notice.